

A60 Lamp Specification

Sales code	LA605E27/827A230A	LA608E27/827A230A	LA608E27D/827A230A	LA6011E27/827A230A	LA6011E27D/827A230A
Rated voltage (V)	220-240	220-240	220-240	220-240	220-240
Rated frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Power factor	0.45	0.67	0.67	0.67	0.67
Rated power (W)	5.0W	7.5W	7.5W	10.5W	10.5W
Power consumption	5kWh/ 1000h	7.5kWh/ 1000h	7.5kWh/ 1000h	10.5kWh/ 1000h	10.5kWh/ 1000h
Rated luminous flux (lm)	350 lm	470 lm	470 lm	806 lm	806 lm
Lamp cap	E27	E27	E27	E27	E27
Equivalent incandescent lamp power	32W	40W	40W	60W	60W
Luminous maintenance factor at the end of the nominal life	70%	70%	70%	70%	70%
Nominal life time (h)	25000	25000	25000	25000	25000
Rated lamp life time (h)	25000	25000	25000	25000	25000
Starting time (s)	0.3s	0.3s	0.3s	0.3s	0.3s
Warm-up time	Instant full light	Instant full light	Instant full light	Instant full light	Instant full light
Number of switching cycles before premature failure	50000	30000	30000	30000	30000
Colour temperature (K)	2700	2700	2700	2700	2700
Colour consistency	<6 steps MacAdam ellipse	<6 steps MacAdam ellipse	<6 steps MacAdam ellipse	<6 steps MacAdam ellipse	<6 steps MacAdam ellipse
Dimmable / non-dimmable	Non-dimmable	Non-dimmable	Non-dimmable	Non-dimmable	Non-dimmable
Operating ambient temperature (°C)	-20°C to +40°C	-20°C to +40°C	-20°C to +40°C	-20°C to +40°C	-20°C to +40°C
Colour rendering (Ra)	80	80	80	80	80
Dimension(mm)	Φ60×110	Φ60×110	Φ60×110	Φ60×110	Φ60×110